



PowerPro™ Engines & Engine-Driven Pumps



CLEANER
Dry up after every 50
hours of use. Wash
out with a soft cloth.

ELECTRONIC IGNITION

**Power
13.0 PRO**

2541-0048

PowerPro™ Gasoline Engines

High Quality, Field-Proven Engine

FEATURES & BENEFITS

- Available in multiple horsepower options to suit a diverse range of agricultural, industrial, and lawn & garden applications
- Electric start option available for quick start-up
- Dual element air filter provides highest degree of filtering
- Cast iron cylinder sleeve for commercial use
- Overhead valve for cleaner operation on most models; flat head on 2.5 HP
- Equipped with a robust low-oil sensor to prevent engine damage
- Choose between CARB/EPA certified or EPA only certified engines
- Engines can be configured to various Hypro pump models or purchased individually
- Supported with a one-year warranty from Hypro; repair parts available for easy servicing
- Dedicated technical and service support: **1-800-POWERPRO**



2.5 HP



6.5 HP








13 HP Electric Start

PowerPro Gasoline Engines, Recoil Start

CARB & EPA Part Number	EPA Part Number	HP	Shaft Size
2549-0043	2549-0044	2.5	5/8" Keyed
-	2549-0042	2.5	1/2" with Flat
2541-0043	2543-0043	5.5	3/4" Keyed
2541-0044	2543-0044	5.5	5/8" Threaded
2541-0052	2543-0052	5.5	2:1 reduced 3/4" Shaft
2541-0045	2543-0045	6.5	3/4" Keyed
2541-0046	2543-0046	6.5	5/8" Threaded
2541-0047	2543-0047	9	1" Keyed
2541-0048	2543-0048	13	1" Keyed
2541-0050	2543-0050	13	1" Threaded

PowerPro Gasoline Engines, Electric Start

CARB & EPA Part Number	EPA Part Number	HP	Shaft Size
2541-0053	2543-0053	6.5	3/4" Keyed
2541-0054	2543-0054	6.5	2:1 reduced 3/4" Shaft
2541-0055	2543-0055	6.5	5/8" Threaded
2541-0056	2543-0056	9	1" Keyed
2541-0049	2543-0049	13	1" Keyed
2541-0051	2543-0051	13	1" Threaded



Polypropylene Transfer Pumps

Lightweight and Versatile Pumps Ideal for Tank Filling and Chemical Transfer

FEATURES & BENEFITS

- Polypropylene housing is suitable for corrosive environments
- Powered by field-proven Hypro® PowerPro™ EPA engine
- Self-priming capabilities with maximum suction lift up to 25 feet/7.62 meters
- Nylon impellers (1542P Series) and poly impellers with stainless steel inserts (1543P Series) can handle solid particles in suspension up to 3/8" diameter
- EPDM mechanical seal and inlet valve for longevity and reliability in most applications
- Available in 2" and 3" models to fit common hose sizes
- Supported with a one-year Hypro® warranty on both pump and PowerPro™ engine
- Pump and engine repair parts available for easy servicing



1542P-65SP



1543P-130SP

Order Information

Model Number	Max GPM	Max PSI	Port Size	Engine Mfg. & HP
1542P-55SP	150	58	2" x 2"	PowerPro 5.5 HP
1542P-65SP	200	58	2" x 2"	PowerPro 6.5 HP
3430-0690	Pump head kit for 1542P-55SP with EPDM seal			
3430-0691	Pump head kit for 1542P-65SP with EPDM seal			
3430-0635	EPDM seal kit for 1542P Series			
1543P-90SP	373	54	3" x 3"	PowerPro 9 HP
1543P-90ESP	373	54	3" x 3"	PowerPro 9 HP w/ elec. start
1543P-130SP	440	54	3" x 3"	PowerPro 13 HP
1543P-130ESP	440	54	3" x 3"	PowerPro 13 HP w/ elec. start
3430-0692	Pump head kit for 1543P series with EPDM seal			
3430-0757	EPDM seal kit for 1543P series			

Hydraulic motor models available. Reference catalog HYP01 for more information.

1542P-55SP

US Standard

GPM at 0 PSI	GPM at 10 PSI	GPM at 20 PSI	GPM at 30 PSI	GPM at 40 PSI	GPM at 50 PSI	GPM at 58 PSI
150	147	131	108	80	48	0

1542P-55SP

Metric

LPM at 0 BAR	LPM at 0.7 BAR	LPM at 1.4 BAR	LPM at 2.1 BAR	LPM at 2.8 BAR	LPM at 3.4 BAR	LPM at 4.0 BAR
568	556	496	409	303	182	0

1542P-65SP

US Standard

GPM at 0 PSI	GPM at 10 PSI	GPM at 20 PSI	GPM at 30 PSI	GPM at 40 PSI	GPM at 50 PSI	GPM at 58 PSI
200	182	162	136	106	65	0

1542P-65SP

Metric

LPM at 0 BAR	LPM at 0.7 BAR	LPM at 1.4 BAR	LPM at 2.1 BAR	LPM at 2.8 BAR	LPM at 3.4 BAR	LPM at 4.0 BAR
757	689	613	515	401	246	0

1543P-90SP, 1543P-90ESP

US Standard

GPM at 0 PSI	GPM at 10 PSI	GPM at 20 PSI	GPM at 30 PSI	GPM at 40 PSI	GPM at 50 PSI	GPM at 54 PSI
373	343	291	231	156	53	0

1543P-90SP, 1543P-90ESP

Metric

LPM at 0 BAR	LPM at 0.7 BAR	LPM at 1.4 BAR	LPM at 2.1 BAR	LPM at 2.8 BAR	LPM at 3.4 BAR	LPM at 3.7 BAR
1412	1298	1102	874	591	201	0

1543P-130SP, 1543P-130ESP

US Standard

GPM at 0 PSI	GPM at 10 PSI	GPM at 20 PSI	GPM at 30 PSI	GPM at 40 PSI	GPM at 50 PSI	GPM at 54 PSI
440	400	338	269	184	68	0

1543P-130SP, 1543P-130ESP

Metric

LPM at 0 BAR	LPM at 0.7 BAR	LPM at 1.4 BAR	LPM at 2.1 BAR	LPM at 2.8 BAR	LPM at 3.4 BAR	LPM at 3.7 BAR
1666	1514	1279	1018	697	257	0

Cast Iron Transfer Pumps

Heavy-Duty Pumps Suitable for Rugged Transfer Applications

FEATURES & BENEFITS

- Cast iron housing and impeller ideal for rugged applications including tank filling and chemical transfer
- Powered by field-proven Hypro® PowerPro™ EPA engines
- Self-priming capabilities with maximum suction lift up to 20 feet/6.1 meters
- Fluoroelastomer seal provides excellent chemical resistance
- Available in 2" and 3" models to fit common hose sizes
- Supported with a one-year Hypro® warranty on both pump and PowerPro™ engine
- Pump and engine repair parts available for easy servicing



1533C-13ESP

Order Information

Model Number	Max GPM	Max PSI	Port Size	Engine Mfg. & HP
1532C-6SP	170	42	2" x 2"	PowerPro 6.5 HP
3430-0673CSP	170	42	Pump head kit for 2" self-priming cast iron transfer pump.	
1533C-9SP	330	66	3" x 3"	PowerPro 9 HP
1533C-13SP	330	66	3" x 3"	PowerPro 13 HP
1533C-13ESP	330	66	3" x 3"	PowerPro 13 HP w/ electric start
3430-0674CSP	330	66	Pump head kit for 3" self-priming cast iron transfer pump.	

Additional drive options available. Reference catalog HYP01 for more information.

1532C-6SP

US Standard

GPM at 0 PSI	GPM at 5 PSI	GPM at 10 PSI	GPM at 15 PSI	GPM at 20 PSI	GPM at 25 PSI	GPM at 30 PSI	GPM at 35 PSI	GPM at 40 PSI	GPM at 42 PSI
170	155	140	123	106	87	65	42	14	0

1532C-6SP

Metric

LPM at 0.0 BAR	LPM at 0.3 BAR	LPM at 0.7 BAR	LPM at 1.0 BAR	LPM at 1.4 BAR	LPM at 1.7 BAR	LPM at 2.1 BAR	LPM at 2.4 BAR	LPM at 2.8 BAR	LPM at 2.9 BAR
644	587	530	466	401	329	246	159	53	0

1533C-9SP, 1533C-13SP, 1533C-13ESP

US Standard

GPM at 0 PSI	GPM at 5 PSI	GPM at 10 PSI	GPM at 15 PSI	GPM at 20 PSI	GPM at 25 PSI	GPM at 30 PSI	GPM at 35 PSI	GPM at 40 PSI	GPM at 45 PSI	GPM at 50 PSI	GPM at 60 PSI	GPM at 66 PSI
330	325	321	315	296	273	248	221	192	161	129	48	0

1533C-9SP, 1533C-13SP, 1533C-13ESP

Metric

LPM at 0.0 BAR	LPM at 0.3 BAR	LPM at 0.7 BAR	LPM at 1.0 BAR	LPM at 1.4 BAR	LPM at 1.7 BAR	LPM at 2.1 BAR	LPM at 2.4 BAR	LPM at 2.8 BAR	LPM at 3.1 BAR	LPM at 3.4 BAR	LPM at 4.1 BAR	LPM at 4.6 BAR
1249	1230	1215	1192	1120	1033	938	836	726	609	488	181	0

Aluminum Transfer Pumps

Lightweight Pumps Ideal for Water Transfer

FEATURES & BENEFITS

- Aluminum housing is suitable for applications of flood water removal, lawn and garden watering and pond filling
- Powered by field-proven Hypro® PowerPro™ EPA engine
- Self-priming capabilities with maximum suction lift up to:
 - 10 feet/3.05 meters (1541A)
 - 23 feet/7.01 meters (1542A/1543A)
- Durable cast iron impeller and diffuser for long life
- Trash pump can handle solid particles in suspension up to 1-1/8" diameter
- EPDM mechanical seal and inlet valve for longevity and reliability in dewatering applications
- Available in 2" and 3" models to fit common hose sizes
- Supported with a one-year Hypro® warranty on both pump and PowerPro™ engine
- Pump and engine repair parts available for easy servicing



1541A-SP



1543A-SP



1543A-TSP

Order Information

Model Number	Max GPM	Max PSI	Port Size	Engine Mfg. & HP
1541A-SP	87.2	40	2" x 2" BSP	PowerPro 2.5 HP
1542A-SP	147	50	2" x 2" BSP	PowerPro 5.5 HP
1543A-SP	259	50	3" x 3" BSP	PowerPro 6.5 HP
1543A-TSP (Trash)	272	50	3" x 3" NPSH	PowerPro 6.5 HP

1541A-SP

US Standard

GPM at 5 PSI	GPM at 10 PSI	GPM at 15 PSI	GPM at 20 PSI	GPM at 25 PSI	GPM at 30 PSI	GPM at 35 PSI	GPM at 40 PSI
87	76	64	51	39	26	8.4	0

1541A-SP

Metric

LPM at 0.3 BAR	LPM at 0.7 BAR	LPM at 1.0 BAR	LPM at 1.4 BAR	LPM at 1.7 BAR	LPM at 2.1 BAR	LPM at 2.4 BAR	LPM at 2.8 BAR
330	288	241	194	146	98	32	0

1542A-SP

US Standard

GPM at 5 PSI	GPM at 10 PSI	GPM at 15 PSI	GPM at 20 PSI	GPM at 25 PSI	GPM at 30 PSI	GPM at 35 PSI	GPM at 40 PSI	GPM at 45 PSI	GPM at 50 PSI
147	144	137	125	110	94	78	57	19.2	0

1542A-SP

Metric

LPM at 0.3 BAR	LPM at 0.7 BAR	LPM at 1.0 BAR	LPM at 1.4 BAR	LPM at 1.7 BAR	LPM at 2.1 BAR	LPM at 2.4 BAR	LPM at 2.8 BAR	LPM at 3.1 BAR	LPM at 3.4 BAR
557	545	517	472	417	356	296	216	73	0

1543A-SP

US Standard

GPM at 5 PSI	GPM at 10 PSI	GPM at 15 PSI	GPM at 20 PSI	GPM at 25 PSI	GPM at 30 PSI	GPM at 35 PSI	GPM at 40 PSI	GPM at 45 PSI	GPM at 50 PSI
259	252	234	214	191	162	136	99	56	8.7

1543A-SP

Metric

LPM at 0.3 BAR	LPM at 0.7 BAR	LPM at 1.0 BAR	LPM at 1.4 BAR	LPM at 1.7 BAR	LPM at 2.1 BAR	LPM at 2.4 BAR	LPM at 2.8 BAR	LPM at 3.1 BAR	LPM at 3.4 BAR
980	952	885	809	723	614	514	376	212	33

1543A-TSP

US Standard

GPM at 5 PSI	GPM at 10 PSI	GPM at 15 PSI	GPM at 20 PSI	GPM at 25 PSI	GPM at 30 PSI	GPM at 35 PSI	GPM at 40 PSI	GPM at 45 PSI	GPM at 50 PSI
272	270	241	208	179	140	98	51	5.4	0

1543A-TSP

Metric

LPM at 0.3 BAR	LPM at 0.7 BAR	LPM at 1.0 BAR	LPM at 1.4 BAR	LPM at 1.7 BAR	LPM at 2.1 BAR	LPM at 2.4 BAR	LPM at 2.8 BAR	LPM at 3.1 BAR	LPM at 3.4 BAR
1030	1021	912	786	679	532	371	192	20	0

Centrifugal Pumps

Non-Positive Displacement Pump and Engine Units

FEATURES & BENEFITS

- Hypro® quality centrifugal pumps powered by field-proven PowerPro™ EPA certified engines
- Self-priming capabilities (-SP models only) with maximum suction lift up to:
 - 15 feet/4.57 meters (1522C Series)
 - 20 feet/6.10 meters (1552C Series)
- Cast iron housing ideal for common agricultural spraying or transfer applications
- Rugged nylon impeller for high density fluid applications
- Viton/ceramic pump seals provide good chemical resistance and extend pump life
- Stainless steel wear ring for extended life in normal chemical spraying applications
- Supported with a one-year Hypro® warranty on both pump and PowerPro™ engine



1521C-65



1522C-65SP

Order Information

Model Number	Max GPM	Max PSI	Port Size	Engine Mfg. & HP
1521C-65	110	80	1 1/2" x 1 1/4"	PowerPro 6.5 HP
1521C-65M	Same as 1521C-65 with mounting base			
1522C-65SP	130	65	2" x 2"	PowerPro 6.5 HP
3430-0332	Seal and O-ring repair kit			
1552C-130	170	150	2" x 1 1/2"	PowerPro 13 HP
1552C-130E	170	150	2" x 1 1/2"	PowerPro 13 HP w/ electric start
1552C-130SP	163	147	2" x 2"	PowerPro 13 HP
1552C-130ESP	163	147	2" x 2"	PowerPro 13 HP w/ electric start
3430-0464	Seal and O-ring repair kit			

1521C-65, 1521C-65M

US Standard

GPM at 0 PSI	GPM at 10 PSI	GPM at 20 PSI	GPM at 30 PSI	GPM at 40 PSI	GPM at 50 PSI	GPM at 60 PSI	GPM at 70 PSI	GPM at 80 PSI
110	110	106	96	88	80	60	30	0

1521C-65, 1521C-65M

Metric

LPM at 0 BAR	LPM at 0.7 BAR	LPM at 1.4 BAR	LPM at 2.1 BAR	LPM at 2.8 BAR	LPM at 3.4 BAR	LPM at 4.1 BAR	LPM at 4.8 BAR	LPM at 5.5 BAR
416	416	401	363	333	303	227	114	0

1522C-65SP

US Standard

GPM at 0 PSI	GPM at 10 PSI	GPM at 20 PSI	GPM at 30 PSI	GPM at 35 PSI	GPM at 40 PSI	GPM at 50 PSI	GPM at 60 PSI	GPM at 65 PSI
130	121	108	93	85	76	56	34	0

1522C-65SP

Metric

LPM at 0 BAR	LPM at 0.7 BAR	LPM at 1.4 BAR	LPM at 2.1 BAR	LPM at 2.4 BAR	LPM at 2.8 BAR	LPM at 3.4 BAR	LPM at 4.1 BAR	LPM at 4.5 BAR
492	458	409	352	322	288	212	129	0

1552C-130, 1552C-130E

US Standard

GPM at 0 PSI	GPM at 20 PSI	GPM at 40 PSI	GPM at 60 PSI	GPM at 80 PSI	GPM at 100 PSI	GPM at 120 PSI	GPM at 140 PSI	GPM at 150 PSI
170	145	130	107	87	69	45	16	0

1552C-130, 1552C-130E

Metric

LPM at 0 BAR	LPM at 1.4 BAR	LPM at 2.8 BAR	LPM at 4.1 BAR	LPM at 5.5 BAR	LPM at 6.9 BAR	LPM at 8.3 BAR	LPM at 9.1 BAR	LPM at 10.3 BAR
644	549	492	405	329	261	170	61	0

1552C-130SP, 1552C-130ESP

US Standard

GPM at 0 PSI	GPM at 20 PSI	GPM at 40 PSI	GPM at 60 PSI	GPM at 80 PSI	GPM at 100 PSI	GPM at 120 PSI	GPM at 140 PSI	GPM at 147 PSI
163	161	148	122	100	75	51	27	0

1552C-130SP, 1552C-130ESP

Metric

LPM at 0 BAR	LPM at 1.4 BAR	LPM at 2.8 BAR	LPM at 4.1 BAR	LPM at 5.5 BAR	LPM at 6.9 BAR	LPM at 8.3 BAR	LPM at 9.7 BAR	LPM at 10.1 BAR
617	609	560	462	379	284	193	102	0

Diaphragm Pumps

Heavy-Duty, Positive Displacement Pump and Engine Units

FEATURES & BENEFITS

- Hypro® quality diaphragm pumps powered by field-proven PowerPro™ EPA certified engines
- Oil-bath design and premium quality synthetic diaphragms provides longer life and greater reliability
- Oil-bath design also allows pump to be run dry
- Self-priming operation
- Corrosive, abrasive and general use chemical compatibility
- Visual oil-level sight glass
- Supported with a one-year Hypro® warranty on both pump and PowerPro™ engine



D252GRGI-25



D30GRGI-65

Order Information

Model Number	Max GPM	Max PSI	Max RPM	Control Unit & Gearbox	Engine Mfg. & HP
D252GRGI-25	5.9	290	3600	9910-KIT1990	PowerPro 2.5 HP
D252GRGI-55	5.9	290	3600	9910-KIT1990	PowerPro 5.5 HP
D30GRGI-65	9.6	580	3600	GS40GI and KIT1640	PowerPro 6.5 HP
D30HRGI-65	9.6	580	3600	GS40GI and 8000-0056	PowerPro 6.5 HP
D30HRGI-65E	9.6	580	3600	GS40GI and 8000-0056	PowerPro 6.5 HP w/ electric start
D403GRGI-65	9.9	580	3600	GR40 and KIT1640	PowerPro 6.5 HP
D403HRGI-65	9.9	580	3600	GR40 and 8000-0056	PowerPro 6.5 HP
D403HRGI-65E	9.9	580	3600	GR40 and 8000-0056	PowerPro 6.5 HP w/ electric start
D503HRGI-65	14.3	290	3600	GR40 and 8000-0056	PowerPro 6.5 HP
D503HRGI-65E	14.3	290	3600	GR40 and 8000-0056	PowerPro 6.5 HP w/ electric start



D403GRGI-65



D503HRGI-65

D252GRGI-25, D252GRGI-55**US Standard**

GPM at 0 PSI	GPM at 72 PSI	GPM at 145 PSI	GPM at 217 PSI	GPM at 290 PSI
5.9	5.0	4.8	4.7	4.6

D252GRGI-25, D252GRGI-55**Metric**

LPM at 0 BAR	LPM at 5 BAR	LPM at 10 BAR	LPM at 15 BAR	LPM at 20 BAR
22	19	18	18	17

D30GRGI-65**US Standard**

GPM at 0 PSI	GPM at 145 PSI	GPM at 290 PSI	GPM at 465 PSI	GPM at 580 PSI
9.6	9.3	8.8	8.6	8.3

D30GRGI-65**Metric**

LPM at 0 BAR	LPM at 10 BAR	LPM at 20 BAR	LPM at 30 BAR	LPM at 40 BAR
36	35	33	33	31

D30HRGI-65, D30HRGI-65E**US Standard**

GPM at 0 PSI	GPM at 145 PSI	GPM at 290 PSI	GPM at 465 PSI	GPM at 580 PSI
9.6	9.3	8.8	8.6	8.3

D30HRGI-65, D30HRGI-65E**Metric**

LPM at 0 BAR	LPM at 10 BAR	LPM at 20 BAR	LPM at 30 BAR	LPM at 40 BAR
36	35	33	33	31

D403GRGI-65**US Standard**

GPM at 0 PSI	GPM at 145 PSI	GPM at 290 PSI	GPM at 465 PSI	GPM at 580 PSI
9.9	9.8	9.7	9.6	9.5

D403GRGI-65**Metric**

LPM at 0 BAR	LPM at 10 BAR	LPM at 20 BAR	LPM at 30 BAR	LPM at 40 BAR
38	37	37	36	36

D403HRGI-65, D403HRGI-65E**US Standard**

GPM at 0 PSI	GPM at 145 PSI	GPM at 290 PSI	GPM at 465 PSI	GPM at 580 PSI
9.9	9.8	9.7	9.6	9.5

D403HRGI-65, D403HRGI-65E**Metric**

LPM at 0 BAR	LPM at 10 BAR	LPM at 20 BAR	LPM at 30 BAR	LPM at 40 BAR
38	37	37	36	36

D503HRGI-65, D503HRGI-65E**US Standard**

GPM at 0 PSI	GPM at 145 PSI	GPM at 290 PSI
14.3	14.1	13.8

D503HRGI-65, D503HRGI-65E**Metric**

LPM at 0 BAR	LPM at 10 BAR	LPM at 20 BAR
54	53	52

Hypro® Gearbox

FEATURES & BENEFITS

- New and improved bolt-through pinion gear helps prevent keyway fretting and ceasing
- Robust 6:1 gear design increases longevity
- Engine mounting flange designed for ease of assembly with standard tools
- Increased oil capacity reduces service time
- Available pre-assembled on HRGI models
- Mounts to D30, D50, D403 and D503 models

**8000-0056**

Roller Pumps

Heavy-duty, Positive-Displacement Pump and Engine Units

FEATURES & BENEFITS

- Hypro® quality roller pumps powered by field-proven PowerPro™ EPA certified engines
- Available with cast iron housing and rotor for common agricultural, pest control, and water wash-down applications, or Silvercast housing and rotor for more corrosion resistance
- Super Rollers™ provide the best chemical resistance and the longest life in most applications
- Viton® seals provide the best overall chemical resistance
- ¾" NPT ports fit most existing sprayer plumbing system
- Supported with a one-year Hypro® warranty on both pump and PowerPro™ engine



4101C-25A

Order Information

Model Number	Max GPM	Max PSI	Engine Mfg. & HP
4101C-25A	8.9	100	PowerPro 2.5 HP
4101XL-25A	8.9	150	PowerPro 2.5 HP

4101C-25A, 4101XL-25A

US Standard

GPM at 0 PSI	GPM at 50 PSI	GPM at 100 PSI	GPM at 150 PSI
8.9	8.6	8.3	8.0

4101C-25A, 4101XL-25A

Metric

LPM at 0 BAR	LPM at 3.4 BAR	LPM at 6.9 BAR	LPM at 10.3 BAR
34	33	31	30

Accessories

BALL VALVES

Hypro ball valves work great in applications where a transfer pump is used.

- 2" single union ball valves available in 2-way full port or 3-way full port with bottom connection
- Reinforced polypropylene body provides strength and resistance in corrosive environments
- Easy lever movement decreases operator strain
- PTFE (Teflon) seals and stainless steel hardware for long lasting performance



Order Information

Model Number	Description
9951-2200N	2" NPT 2-way Single Union Ball Valve
9951-3200N	2" NPT 3-way Single Union Ball Valve

Additional sizes available. Reference catalog HYP01 for more information.



CAM LOCK FITTINGS

Hypro cam lock fittings allow for quick and easy hose attachment to the transfer pump for the ultimate in convenience.

- Stainless steel locking levers provide for maximum mechanical strength and corrosion resistance
- Interchangeable with other cam lock couplings made to MIL-C-27487 specifications
- Locking mechanism available to prevent accidental opening

Order Information

Size	Pump-End Fitting	Hose-End Fitting
2"	9950-200NF	9950-200C
3"	9950-300NF	9950-300C

Additional sizes available. Reference catalog HYP01 for more information.



“Value Beyond The Pump”



Contact Hypro for all of your spraying needs:

- Online www.hypropumps.com
- Technical/Application 800-445-8360
- Order Department 800-42HYPRO (800-424-9776)
- FAX for fast delivery 800-323-6496



Pentair

SPRAY & INJECTION TECHNOLOGIES GROUP

375 Fifth Avenue NW • New Brighton, MN 55112
Phone: (651) 766-6300 • 800-424-9776 • Fax: 800-323-6496

www.hypropumps.com