



Quick TeeJet® Adapters and Accessories

QJ1/4T-NYB & QJT-NYB

- QJ1/4T-NYB allows use of Quick TeeJet system with 1/4" NPT and BSPT male connections.
- QJT-NYB permits use of Quick TeeJet system with standard 1/16"-16 TeeJet thread.
- Maximum operating pressure of 300 PSI (20 bar).

PART NUMBER	TO FIT
(B)QJ1/4T-NYB	1/4" (F) thread

(B)=BSPT



QJ90-2-NYR

- Fits standard Quick TeeJet bodies.
- Made of Nylon with CP19438-EPR gasket (included).
- Use with Quick TeeJet cap and gasket for automatic alignment when using flat fan spray tips.
- 90° included angle between outlets. When used with standard flat fan tips produces a twin type spray pattern for improved coverage and canopy penetration.

PART NUMBER	TO FIT
QJ90-2-NYR	Quick TeeJet

QJ1/4TT-NYB

- Allows use of Quick TeeJet system with 1/4" NPT and BSPT female connections.
- Maximum operating pressure of 300 PSI (20 bar).

PART NUMBER	TO FIT
QJ(B)1/4TT-NYB	1/4" (M) thread

(B)=BSPT



22674-1/4-NYB

- Allows use of Quick TeeJet system with 1/4" NPT female connections.

PART NUMBER	TO FIT
22674-1/4-NYB	1/4" (M) thread

QJT8360-NYB, QJP19011-NYB, QJ8360-NYB

- Retrofits to a Quick TeeJet system.
- Features ChemSaver® no-drip shutoff. Requires 10 PSI (0.7 bar) at the nozzle to open check valve.
- Standard diaphragm of EPDM with optional Viton® available upon request.
- Maximum operating pressure of 300 PSI (20 bar).

PART NUMBER	TO FIT
QJ(B)8360-NYB	1/4" (M) thread
QJT8360-NYB	1/16"-16 TeeJet thread
QJP19011-NYB	3/8" BSPP thread

(B)=BSPT



QJ8355-NYB

- Allows use of Quick TeeJet system with 1/8" and 1/4" NPT female connections.
- Side mounting provides protection of the nozzle body.
- Features ChemSaver no-drip shutoff. Requires 10 PSI (0.7 bar) at the nozzle to open check valve.
- Standard diaphragm of EPDM with optional Viton available upon request.
- Maximum operating pressure of 300 PSI (20 bar).

PART NUMBER	TO FIT
QJ8355-1/8-NYB	1/8" (F)
QJ8355-1/4-NYB	1/4" (F)



Quick TeeJet® Caps for Hardi Nozzle Bodies

Color Code

1	2	3	4	5	6	7	8
Black	White	Red	Blue	Green	Yellow	Brown	Orange

Ordering Information

QUICK TEEJET CAPS	PART NUMBER		FOR USE WITH FLAT SPRAY TIPS 150 PSI (10 BAR) MAXIMUM PRESSURE						
	QUICK TEEJET CAP ONLY	QUICK TEEJET CAP & SEAT GASKET SET	TJ TwinJet®	AI TeeJet® & AIUB TeeJet®	SJ-3 StreamJet®	DG TwinJet®	Turbo TeeJet® Induction		
	CP21399-*.CE	21398H-*.CELR							
	CP23307-*.CE	23306H-*.CELR	TeeJet Flat Spray Tips (Smaller Capacities)						
			Standard -0067 Thru -08	XR -01 Thru -08	AIXR TeeJet®	DG TeeJet®	TT	OC TeeJet® -01 Thru -08	Turbo TeeJet®

Note: When using TeeJet tip strainer, use CP26227 gasket in place of CP23308 gasket.